



**HAL**  
open science

# Center of mass velocity comparison using a whole body magnetic inertial measurement unit system and force platforms in well trained sprinters in straight-line and curve sprinting

Benjamin Millot, Paul Blache, Daniel Dinu, Axelle Arnould, Jérémy Jusseaume, Christine Hanon, Jean Slawinski

## ► To cite this version:

Benjamin Millot, Paul Blache, Daniel Dinu, Axelle Arnould, Jérémy Jusseaume, et al.. Center of mass velocity comparison using a whole body magnetic inertial measurement unit system and force platforms in well trained sprinters in straight-line and curve sprinting. *Gait&Posture*, 2022, 99, pp.90-97. 10.1016/j.gaitpost.2022.11.002 . hal-03874545

**HAL Id: hal-03874545**

**<https://insep.hal.science/hal-03874545>**

Submitted on 28 Nov 2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Center of mass velocity comparison using a whole body magnetic inertial measurement unit system and force platforms in well trained sprinters in straight-line and curve sprinting

Benjamin Millot<sup>a,b</sup>, Paul Blache<sup>a</sup>, Daniel Dinu<sup>a</sup>, Axelle Arnould<sup>a</sup>, Jérémy Jusseaume<sup>a</sup>, Christine Hanon<sup>b</sup>,  
Jean Slawinski<sup>a</sup>

<sup>a</sup>Laboratory Sport, Expertise and Performance (EA7370), French Institute of Sport (INSEP), 11, Avenue du Tremblay, 75012 Paris, France. [benjamin.millot@insep.fr](mailto:benjamin.millot@insep.fr);  
[paulblache91@gmail.com](mailto:paulblache91@gmail.com); [daniel.dinu@insep.fr](mailto:daniel.dinu@insep.fr); [aarnould.insep@gmail.com](mailto:aarnould.insep@gmail.com);  
[j.jusseaume92@gmail.com](mailto:j.jusseaume92@gmail.com); [jean.slawinski@insep.fr](mailto:jean.slawinski@insep.fr)

<sup>b</sup>French Athletics Federation (FFA), 33, Avenue Pierre de Coubertin, 75013 Paris, France.  
[benjamin.millot@athle.fr](mailto:benjamin.millot@athle.fr); [christine.hanon@athle.fr](mailto:christine.hanon@athle.fr)

Corresponding author: Benjamin Millot; +33 (0) 1 41 74 41 03; [benjamin.millot@insep.fr](mailto:benjamin.millot@insep.fr); 11, Avenue du Tremblay, 75012 Paris; [benjamin.millot@athle.fr](mailto:benjamin.millot@athle.fr); 33, Avenue Pierre de Coubertin, 75013 Paris, France.

## - Acknowledgments

The authors give special thanks to Vincent Guyot and Iwen Diouron for their assistance with data collection for this study and Sarah Chauchard for their help with English editing. We would also like to thank DimaSport for their support in reconstructing the curve and all the athletes from the present experimentation for their thorough involvement over each one's session. Benjamin Millot received a PhD scholarship (CIFRE contract n°2019/1904) funded by the French Athletics Federation and the French Agency of Research and Technology.

## Abstract:

**Background:** Sprint performance can be characterized through the centre of mass (COM) velocity over time. *In-field* computation of the COM is key in sprint training. **Research question:** To compare the stance-averaged COM velocity computation from a Magneto-Inertial Measurement Units (MIMU) to a reference system: force platforms (FP), over the early acceleration phase in both straight and curve sprinting. **Methods:** Nineteen experienced-to-elite track sprinters performed 1 maximal sprint on both the straight and the curve (radius = 41.58 m) in a randomized order. Utilizing a MIMU-based system (Xsens MVN Link) and compared to FP (Kistler), COM velocity was computed with both systems. Averaged stance-by-stance COM velocity over straight-line and curve sprinting following the vertical axis (respectively  $V_{zMIMU}$  and  $V_{zFP}$ ) and the norm of the two axes lying on the horizontal plane: x and y, approximately anteroposterior and mediolateral (respectively  $V_{xyMIMU}$  and  $V_{xyFP}$ ) over the starting-blocks (SB) and initial acceleration (IA – composed out of the first four stances following the SB) were compared using mean bias, 95% limits of agreements and Pearson's correlation coefficients. **Results:** 148 stances were analyzed.  $V_{xyMIMU}$  mean bias was comprised between 0.26 and 2.03% (expressed in % with respect to the FP) for SB, 5.63 and 7.29% over IA respectively on the straight and the curve. Pearson's correlation coefficients ranged between 0.943 and 0.990 for  $V_{xy}$ , 0.423 and 0.938 for  $V_z$ . On the other hand,  $V_{zMIMU}$  mean bias ranged between 2.33 and 4.69% for SB, between 1.44 and 19.95% over IA respectively on the straight and the curve. **Significance:** The present findings suggest that the MIMU-based system tested slightly underestimated  $V_{xyMIMU}$ , though within narrow limits which supports its utilization. On the other hand,  $V_{zMIMU}$  computation in sprint running is not fully mature yet. Therefore, this MIMU-based system represents an interesting device for *in-field*  $V_{xyMIMU}$  computation either for straight-line and curve sprinting.

Abstract words count: 297.

Manuscript words count: 3156.

Keywords: Magneto-Inertial Measurement Units, curve sprinting, acceleration, force platforms, sprint running.

## 1. Introduction

Sprint performance can be characterized through the centre of mass (COM) velocity over time [1-2]. For this reason, it is of interest to easily evaluate COM kinematics with accuracy within the athletes' ecological environment to preserve the measures' ecological validity. Yet, analyzing accurately the human movement *in-field* remains an everyday challenge especially within the curve. In fact, sprinting in the curve represents ~58% of the total distance for all track events starting from the 200 m (World Athletics, 2019). Unfortunately, within the curve, systems such as radars or lasers become immediately inoperable. A few experimentations have described COM velocity in curve sprinting at specific instants [4-7]; however, the literature describing the COM velocity within this sprinting condition remains limited. Therefore, it is of importance to look for *in-field* devices able to quickly evaluate the COM velocity within the curve over an entire sprint. Outside the laboratory, deciding which device to use relies on a trade-off between accuracy and feasibility. Considering their portability, convenience and range, full-body magneto-inertial measurement unit systems (MIMU) have become popular over the past decade. Yet, several authors have highlighted the limitations of such systems and overall there is no consensus regarding MIMU-based system's concurrent validity against reference systems for joints and segments kinematics [8–15].

At the COM, comparison between a MIMU-based system and an opto-electronic systems (OS) COM position while standing still showed a difference in the measurement from 0.73 mm (vertical axis) to 5.45 mm (medio-lateral axis) as well as very high correlations ( $r > 0.99$ ;  $p < 0.001$ ) [16].

Based on Newton's second law, force platforms (FP) have been considered as the reference system for COM velocity computation in sprint running [17–21], since correct computation does not rely on either accurate marker positioning or assumptions regarding the anthropometrical properties [22–25].

Using FP, Pavei et al. (2020) computed the COM displacement during overground walking and compared to a MIMU-based system [26]. They found differences between systems up to  $98.7 \pm 60.2\%$  [26], likely resulting from the sensors drift and the anthropometrical assumptions.

In sprint running, computations of the force-velocity profiles (FVP) from a MIMU-based system to a radar showed good agreements between both systems for the maximal velocity and the maximal theoretical force, velocity and power ( $0.81 < r < 0.97$ ) [27]. However, despite their broad utilization for straight-line sprinting velocity computation [28–31], radars do not estimate neither the COM nor the frontal plane velocity, but only the participants' horizontal velocity [32-33]. Moreover, measurement can be impaired with such devices since radars detect all moving objects within their field of view.

Other authors used a single MIMU attached to the lumbar region to compute the participants' velocity [34] and compared the FVP variables obtained with those from the FP. Although these authors found “very large” to “extremely large” correlations for all but one FVP variable, they did not investigate the stance-averaged velocity itself. They also evaluated a point close to the COM, probably leading to erroneous COM estimation [22,25,33,35].

Recently, van den Tillaar et al. (2021) compared the step- velocity over 50-m sprints from a MIMU-based system to FP [36]. However, they multiplied step length and step rate rather than comparing the COM velocity, even though this parameter was found to be determinant for sprinting performance [2] and can be used to adapt training programs through FVP computation [21,37].

To our knowledge, no study compared the stance-averaged COM velocity computed from a MIMU-based system to a reference system. Additionally, the few experimentations that compared a MIMU-based system to the reference systems for other parameters only investigated the straight, notwithstanding the curve. Considering the prevalence of this sprinting condition in athletics, it appears mandatory to look for *in-field* devices able to easily evaluate the COM velocity within ecological environment.

Thus, the aim of the present study was to compare the stance-averaged COM velocity computed from a MIMU-based system to FP over the starting-blocks pushing phase and the initial acceleration during both straight-line and curve sprinting.

## 2. Methods

### a) Participants

Nineteen (15 male and 4 female) experienced-to-elite curve sprinters (mean  $\pm$  SD: age =  $23.9 \pm 3.7$  years; body mass =  $73.9 \pm 7.4$  kg; height =  $1.78 \pm 0.07$  m) volunteered to participate in this study. The mean personal bests (PB) of the 6 male 200-m specialists, the 9 male 400-m specialists, the 2 female 200-m specialists and the 2 female 400-m specialists were respectively: 22.89, 49.56, 26.30 and 57.67 s. After an explanation of the protocol, the participants signed the informed consent to participate in the experimentation, conducted in accordance with the declaration of Helsinki and approved by the local ethical committee (IRB00012476-2021-29-04-107).

### b) Materials

#### - Concurrent system

The participants were equipped with a MIMU-based system MVN Link (Xsens Technologies, Enschede, Netherlands, 240 Hz). This system is composed of 17 MIMUs (36 x 24.5 x 10 mm: 10 g) fixed to the participants with straps. Each sensor contains a 3D gyroscope ( $\pm 2000$  °/s), a 3D accelerometer (scale:  $\pm 160$  m/s<sup>2</sup>) and a 3D magnetometer ( $\pm 1.9$  Gauss). Sensors were placed according to the manufacturer's recommendations (see figure 1). Participants' height and foot length were measured and inputted into the MVN software which estimated segment lengths with regression equations [38], [39]. The calibration process was then performed according to the manufacturer instructions and general guidelines [9-10,12] to generate sensor-to-segment alignment [38].

## FIGURE 1

### - Reference system

Using OS, errors can originate from marker positioning, movement on soft tissues and assumptions associated with anthropometric models [22,25-26]. Therefore, in the present experimentation we used a 6.60 m-long FP composed out of 6 individual FP (5 length-wise and 1 sideways; 1.2 x 0.6 m each, KI 9067; Kistler, Wintherthu, Switzerland, 1 000 Hz) as the reference system. FP were connected in series, covered with a tartan mat and embedded within the track, thus making them invisible to the participants. This set-up allowed for a quasi *in-field* experimentation. Anteroposterior, mediolateral and vertical components (respectively  $F_x$ ,  $F_y$  and  $F_z$ ) of the GRF were computed from these FP.

The MIMU-based system and FP signals were synchronized to the nearest MIMU-based system frame using a customised cable with the MIMU-based system software triggering the FP. Accurate synchronization between devices has been confirmed during pilot experimentations by gently pressing on one MIMU positioned over the FP and by checking temporal events of vertical GRF and the MIMU accelerations.

### c) Protocol

The recordings took place on an indoor track between June and July 2021, which corresponded to the competition period. The participants began with at least a 45-min self-managed warm-up. They were then equipped with the MIMUs and had a 10-min additional familiarization period with the MIMUs on. Subsequently, participants performed a maximal “valid” 10-m sprint within two conditions in a randomized order: straight and curve. A replicated curve corresponding to the lane 5 (radius 41.58 m) of a standard athletics track (World Athletics, 2019) overlapped the FP area.

A sprint was considered “valid” when at least the first stance out of the blocks fully landed within the FP area [20-21]. All participants used starting-blocks (SB) that were positioned on the FP which allowed the GRF computation over the SB pushing-phase.

d) Data analysis

- Concurrent system

Using the temporal synchronization between systems, touchdown (TD) and toe-off (TO) for both systems were determined from the FP data using a 20-N threshold on  $F_z$  [37].

MIMU-based system anteroposterior, mediolateral and vertical instantaneous COM velocities (respectively  $V_{xMIMU}$ ,  $V_{yMIMU}$  and  $V_{zMIMU}$ ) based on the manufacturer’s proprietary sensor fusion algorithm were retrieved directly from the MVN software.  $V_{xMIMU}$ ,  $V_{yMIMU}$  and  $V_{zMIMU}$  were low-pass filtered (20-Hz cut-off, third-order zero-phase Butterworth filter) chosen after residual analysis [40].

Thereafter, although the MIMU-based system calibration was realized such that its coordinate system coincides with that of FP, both devices’ coordinate systems are unlikely to be perfectly aligned. Consequently, we computed the norm of the horizontal plane of the MIMU-based system COM velocity ( $V_{xyMIMU}$ ):

$$V_{xyMIMU} = \sqrt{V_{xFP}^2 + V_{yFP}^2} \quad 1$$

- Reference system

GRF raw signals were low-pass filtered (200-Hz cut-off, third-order zero-phase Butterworth filter) chosen after residual analysis [40].

Based on Newton’s Second Law and according to previous literature [17,19–21,23,25-26,41] the three COM orthogonal acceleration components were calculated by dividing GRF by the body mass ( $-m \cdot g$  for the vertical acceleration). Thereafter, we computed instantaneous anteroposterior ( $V_{xFP}$ ),



mediolateral ( $V_{yFP}$ ) and vertical ( $V_{zFP}$ ) velocities by simple integration of the three orthogonal acceleration components over each stance:

$$V_{xFP} = V_{0xFP} + \int \frac{F_x}{m} dt \quad 2$$

$$V_{yFP} = V_{0yFP} + \int \frac{F_y}{m} dt \quad 3$$

$$V_{zFP} = V_{0zFP} + \int \frac{F_z - m \cdot g}{m} dt \quad 4$$

with,  $m$  the participant's body mass,  $V_{0xFP}$ ,  $V_{0yFP}$  and  $V_{0zFP}$  the initial velocity conditions taken as integration constants and set to 0 since SB were placed over the FP and the sprinters started from a stationary position.

Finally, we computed the norm of the horizontal plane of the FP COM velocity ( $V_{xyFP}$ ):

$$V_{xyFP} = \sqrt{V_{xFP}^2 + V_{yFP}^2} \quad 5$$

Analysis was split within two conditions (figure 3), a) the SB phase (which includes only the starting-blocks pushing phase) and b) the initial acceleration, thereafter referred as IA (beginning at the first touchdown after the SB phase and ending at toe-off of the last stance computed).

The norm of the horizontal plane COM velocity ( $V_{xy}$ ) and the vertical COM velocity ( $V_z$ ) computed from both the FP and the MIMU-based system were averaged over each "valid" stance.

#### e) Statistical analysis

All descriptive statistics are presented as means  $\pm$  standard deviations (SD). Normality of the distribution was verified using the Shapiro-Wilk test. Then,  $V_{xy}$  and  $V_z$  obtained with both devices were compared using a) mean bias (expressed in % in comparison to the FP) and 95% limits of agreement [42]; b) Pearson's correlation coefficient ( $r$ ) with threshold values of 0.3, 0.5, 0.7 and 0.9 representing

respectively low, moderate, high and very high relationships [43,44]. For all statistical analyses, the alpha level was set as  $p = 0.05$ .

### 3) Results

The number of valid stances for each participant varied between two (SB and the following stance) to five (SB and the following four stances) for both sprinting conditions. Overall, 75 and 73 valid stances were computed respectively for the straight and the curve.

Table 1 presents the mean  $\pm$  SD for the sprint variables of both systems within the straight and the curve conditions for the SB and IA phases as well as the mean bias, 95% agreement limits and correlation coefficients.

TABLE 1

Figure 2 and 3 display the Bland & Altman plots respectively for SB and IA. Mean bias between the MIMU-based system and the FP was lower on the straight than the curve. Mean  $V_{zMIMU}$  showed a bias of 1.44 and 19.95% respectively on the straight and the curve with random errors up to 108%. Correlation coefficients between devices ranged between  $r = 0.943 < r < 0.990$  for  $V_{xy}$  and  $0.423 < r < 0.938$  for  $V_z$ .

FIGURE 2

### 4) Discussion

This experimentation compared the COM stance-averaged velocity measured from a MIMU-based system to 6 FP over the early acceleration phase in both straight-line and curve sprinting among 19 experienced-to-elite curve sprinters with different anthropometric characteristics, sprinting expertise and mechanical capacities.  $V_{xyMIMU}$  mean bias either for SB (respectively 0.26 and 2.03% for the straight and the curve) and IA (respectively 5.63 and 7.29% for the straight and the curve) was low. Further, correlation coefficients for  $V_{xy}$  were very high for both SB and IA ( $r > 0.943$ ). These correlation

coefficients show that although slightly underestimated, a change of magnitude of  $V_{xyFP}$  is very well associated with a similar change of magnitude of  $V_{xyMIMU}$  either during SB and IA.

### FIGURE 3

Throughout IA, we did not find any trend for the mean bias with increasing  $V_{xy}$ . The last stances'  $V_{xy}$  were  $\sim 5\text{-}6 \text{ m}\cdot\text{s}^{-1}$  which corresponded to  $\sim 60\text{-}70\%$  of the **participants'** maximal velocity. Those findings suggest that differences between systems would not increase **with velocity** although further experimentations evaluating  $V_{xy}$  later on during the acceleration phase or at maximal velocity are needed to confirm our findings.

**Contrastingly**,  $V_{zMIMU}$  showed a greater mean bias (up to  $\sim 20\%$ ) with large limits of agreement (up to  $\sim 108\%$ ). Despite very high correlation coefficients for the SB between devices, IA showed small correlation coefficients meaning that a change of magnitude in  $V_{zFP}$  is poorly associated with a change of magnitude in  $V_{zMIMU}$  over the IA.

### FIGURE 4

The findings of the present experimentation for  $V_{xyFP}$  over the SB and the first two stances are slightly below those reported by Nagahara et al. (2020) among male sprinters (100-m time PBs:  $11.27 \pm 0.27$  s) [45]. In their experimentation, Nagahara et al. (2020) found a  $V_{xyFP}$  of respectively 3.92, 4.93, 5.70 and  $6.30 \text{ m}\cdot\text{s}^{-1}$  for the first, second, third and fourth stances following the SB phase [45] while we found a  $V_{xyFP}$  of respectively 3.59, 4.62, 5.36 and  $6.02 \text{ m}\cdot\text{s}^{-1}$  for the corresponding stances. Considering their athletes' PBs and that all participants were male in their experimentation, the findings of the present experimentation are thus in line with those of Nagahara et al. (2020). Regarding  $V_{zFP}$ , to our knowledge, no experimentation investigated the mean vertical velocity over the first stances. Slawinski et al. (2020) found vertical velocities of 0.52, 0.35 and  $0.35 \text{ m}\cdot\text{s}^{-1}$  among elite sprinters respectively at SB clearing, first and second stances toe-off [27] while we found mean  $V_{zFP}$  of 0.44, 0.19 and  $0.24 \text{ m}\cdot\text{s}^{-1}$  for the corresponding stances.

## FIGURE 5

To the best of our knowledge, only one study compared the step velocity between a MIMU-based system and FP [36]. These authors found that the MIMU-based system velocity was underestimated for all steps. They reported a mean bias from 0.45 to over 0.60 m.s<sup>-1</sup> as opposed to 0.26 m.s<sup>-1</sup> in the present study. These discrepancies likely result from the different methods used to compute the velocity. While we have simply retrieved the COM velocity from the MIMU-based system software, these authors have multiplied step length and step frequency, determined from ankle angular velocity to identify TD and TO using MIMUs placed on both feet, yet based on currently unpublished algorithm [36].

Moreover, when comparing data computed from a MIMU-based system and to those obtained with FP, care must be taken with regards to the coordinate system orientation. The MIMU-based system antero-posterior axis is likely neither aligned with the FP coordinate system nor with the sprinting path. Van den Tilaar et al. (2021) may have considered the antero-posterior axis only. To ensure accurate calculation it is therefore mandatory to compute the norm of the horizontal and mediolateral velocities ( $V_{xyMIMU}$  in the present study) which represents a limitation of this system if someone is willing to analyze each axis distinctly on the field.

Overall, the mean bias found in the present experimentation lies within similar range to those reported by Samozino et al. (2016) in their field method validation. They found absolute bias ranging from ~2 to 8% against FP [21]. These authors concluded that this bias was “low” and this method is widely used in sport science and sprint training since. Similarly, differences between two reference systems (FP and OS) compared together for the COM trajectory reached ~9% in walking at constant speed [26]. Those results show that even with two “reference systems”, differences - likely due to anthropometrical assumptions - comparable to the present findings can be found. Therefore, the present experimentation provides hints in the choice of the optimal system considering their cost, accuracy and easy-of-use ratio that meet the requirement of the experimental conditions.

$V_{zMIMU}$  displayed the largest systematic bias (up to ~20%) and random errors (up to ~108%). Those results are in contrast with the findings of Pavei et al. (2020) who found the lowest bias on the vertical axis [26]. However, they compared the point-by-point root mean square distance, range of motion, minimum and maximum positions on the 3 orthogonal axes [26] while we analyzed the stance-averaged velocities in the present experimentation. Further, these authors have used a different system, sampling at 60 Hz with wireless MIMUs which can account for some of the variance between the experimentations [10]. Finally, their protocol also differed from ours since they analyzed walking strides with constant velocities of  $0.79 \div 1.94 \text{ m}\cdot\text{s}^{-1}$  [26] while we evaluated accelerated sprinting (velocities up to  $\sim 6 \text{ m}\cdot\text{s}^{-1}$ ). It is also important to note that since  $V_{zFP}$  values are much lower than  $V_{xyFP}$ , an error of  $0.05 \text{ m}\cdot\text{s}^{-1}$  would yield greater discrepancies when expressed in percentage. However, considering the large random errors as well as the small correlation coefficients, it must be acknowledged that this MIMU-based system is not fully mature yet for accurately computing  $V_{zMIMU}$  in sprint running.

Other points likely resulting in differences between the FP and the MIMU-based system are worth mentioning. First and foremost, the anthropometrical model used with the MIMU-based system represents one of the main source of errors arising from either OS or MIMU-based systems in comparison to FP [15,25-26]. Although not one of the aims of this study, mean bias was greater for female than male: 4.64% for male and 8.23% for female over IA within the straight. While this shed some light on the possibility that this MIMU-based system anthropometric model is more adapted to male, this must be interpreted cautiously since only 4 females participated in this study.

The differences between the FP and the MIMU-based system should also be balanced since this experimentation focussed on the early acceleration phase, where sprinters produce their greatest acceleration [2]. In addition, at this very time of the sprint, participants are in a crouched-to-semi-straightened position which could challenge the biomechanical model computation. Therefore, the COM velocity of both systems should also be compared when the participant has straightened up.

Discrepancies between **devices** could also result from the **systems' synchronization and the** different sampling rate. Since synchronization between systems was at the nearest **MIMU-based system's** frame, we have tested on two random **participants** what could be the differences for  $V_{xyMIMU}$  with plus or minus 1 frame. We found mean discrepancies of  $\sim 3.5\%$  and maximum **differences** reaching  $\sim 8.5\%$ , which could also **account for** some of the differences between systems.

**MIMU-based system** sensitivity to magnetic fields has also been widely discussed [10,12]. It is of importance to avoid ferromagnetic objects nearby the analysis area to limit sensors drift and ensure following guidelines for **MIMU-based system** use [10]. Considering the wooden indoor stadium where the experimentation took place and **that the FP were** embeded underneath the track surface, we can assume that this likely resulted in little disturbances.

The last source of discrepancy between **the MIMU-based system** and **the** FP could result from FP measurement errors. Albeit considered a **reference system** with pros well detailed by Pavei et al. (2017), FP can also be prone to measurement errors related mainly to a) integration with errors originating from the initial conditions and b) long recordings leading up to FP drift [25].

## 5) Conclusion

Evaluating the COM kinematics within *in-field* environments is a challenging process, especially when seeking for portable system you can use either inside or outside, with a simple setup and a wide range to capture the entire motion. This experimentation brings new insight into the use of this **MIMU-based system** as a valuable alternative of FP or OS for *in-field* **computation of**  $V_{xy}$  over the starting-blocks and the initial acceleration phase be it on the straight or the curve. Further, this **MIMU-based system** would provide the unique opportunity to access  $V_{xy}$  over an entire sprint, be it a 200 or 400-m sprint. **Contrastingly**,  $V_{zMIMU}$  computation is not fully mature yet and further improvement must be made in order for this **MIMU-based system** to become an alternative to **reference system** for this parameter.

## 7) Conflict of interest statement

Declaration of interest: none.

## REFERENCES:

- [1] J. P. Hunter, R. N. Marshall, and P. J. McNair, 'Relationships between Ground Reaction Force Impulse and Kinematics of Sprint-Running Acceleration', *Journal of Applied Biomechanics*, vol. 21, no. 1, pp. 31–43, Feb. 2005, doi: 10.1123/jab.21.1.31.
- [2] J. Slawinski *et al.*, 'Kinematic and Kinetic Comparisons of Elite and Well-Trained Sprinters During Sprint Start', *Journal of Strength and Conditioning Research*, vol. 24, no. 4, pp. 896–905, Apr. 2010, doi: 10.1519/JSC.0b013e3181ad3448.
- [3] D. Wilson and IAAF, Eds., *Track and field facilities manual: 2008 edition; IAAF requirements for planning, constructing, equipping and maintaining*. Monaco: Editions EGC, 2008.
- [4] S. M. Churchill, A. I. T. Salo, and G. Trewartha, 'The effect of the bend on technique and performance during maximal effort sprinting', *Sports Biomechanics*, vol. 14, no. 1, pp. 106–121, Jan. 2015, doi: 10.1080/14763141.2015.1024717.
- [5] S. M. Churchill, A. I. T. Salo, and G. Trewartha, 'The effect of the bend on technique and performance during maximal effort sprinting', *Sports Biomechanics*, vol. 14, no. 1, pp. 106–121, Jan. 2015, doi: 10.1080/14763141.2015.1024717.
- [6] K. Ishimura and S. Sakurai, 'Asymmetry in Determinants of Running Speed During Curved Sprinting', *Journal of Applied Biomechanics*, vol. 32, no. 4, pp. 394–400, Aug. 2016, doi: 10.1123/jab.2015-0127.
- [7] L. J. Judson, S. M. Churchill, A. Barnes, J. A. Stone, I. G. A. Brookes, and J. Wheat, 'Horizontal force production and multi-segment foot kinematics during the acceleration phase of bend sprinting', *Scand J Med Sci Sports*, vol. 29, no. 10, pp. 1563–1571, Oct. 2019, doi: 10.1111/sms.13486.
- [8] S. Blair, G. Duthie, S. Robertson, W. Hopkins, and K. Ball, 'Concurrent validation of an inertial measurement system to quantify kicking biomechanics in four football codes', *Journal of Biomechanics*, vol. 73, pp. 24–32, May 2018, doi: 10.1016/j.jbiomech.2018.03.031.
- [9] V. Camomilla, E. Bergamini, S. Fantozzi, and G. Vannozzi, 'In-field use of wearable magneto-inertial sensors for sports performance evaluation', *ISBS*, 2015.
- [10] V. Camomilla, E. Bergamini, S. Fantozzi, and G. Vannozzi, 'Trends Supporting the In-Field Use of Wearable Inertial Sensors for Sport Performance Evaluation: A Systematic Review', *Sensors*, vol. 18, no. 3, p. 873, Mar. 2018, doi: 10.3390/s18030873.
- [11] A. I. Cuesta-Vargas, A. Galán-Mercant, and J. M. Williams, 'The use of inertial sensors system for human motion analysis', *Physical Therapy Reviews*, vol. 15, no. 6, pp. 462–473, Dec. 2010, doi: 10.1179/1743288X11Y.0000000006.
- [12] G. T. G. Hughes, V. Camomilla, B. Vanwanseele, A. J. Harrison, D. T. P. Fong, and E. J. Bradshaw, 'Novel technology in sports biomechanics: some words of caution', *Sports Biomechanics*, pp. 1–9, Apr. 2021, doi: 10.1080/14763141.2020.1869453.
- [13] P. Macadam, J. Cronin, J. Neville, and S. Diewald, 'Quantification of the validity and reliability of sprint performance metrics computed using inertial sensors: A systematic review', *Gait & Posture*, vol. 73, pp. 26–38, Sep. 2019, doi: 10.1016/j.gaitpost.2019.07.123.



- [14] B. Pedro, S. Cabral, and A. P. Veloso, ‘Concurrent validity of an inertial measurement system in tennis forehand drive’, *Journal of Biomechanics*, vol. 121, p. 110410, May 2021, doi: 10.1016/j.jbiomech.2021.110410.
- [15] X. Robert-Lachaine, H. Mecheri, C. Larue, and A. Plamondon, ‘Validation of inertial measurement units with an optoelectronic system for whole-body motion analysis’, *Med Biol Eng Comput*, vol. 55, no. 4, pp. 609–619, Apr. 2017, doi: 10.1007/s11517-016-1537-2.
- [16] D. Dinu, M. Fayolas, M. Jacquet, E. Leguy, J. Slavinski, and N. Houel, ‘Accuracy of Postural Human-motion Tracking Using Miniature Inertial Sensors’, *Procedia Engineering*, vol. 147, pp. 655–658, 2016, doi: 10.1016/j.proeng.2016.06.266.
- [17] G. A. Cavagna, ‘Force platforms as ergometers’, *Journal of Applied Physiology*, vol. 39, no. 1, pp. 174–179, Jul. 1975, doi: 10.1152/jappl.1975.39.1.174.
- [18] G. A. Cavagna, L. Komarek, and S. Mazzoleni, ‘The mechanics of sprint running’, *The Journal of Physiology*, vol. 217, no. 3, pp. 709–721, Sep. 1971, doi: 10.1113/jphysiol.1971.sp009595.
- [19] H. Elftman, ‘The force exerted by the ground in walking’, *Arbeitsphysiologie*, vol. 10, no. 5, pp. 485–491, May 1939, doi: 10.1007/BF02012165.
- [20] G. Rabita *et al.*, ‘Sprint mechanics in world-class athletes: a new insight into the limits of human locomotion: Sprint mechanics in elite athletes’, *Scand J Med Sci Sports*, vol. 25, no. 5, pp. 583–594, Oct. 2015, doi: 10.1111/sms.12389.
- [21] P. Samozino *et al.*, ‘A simple method for measuring power, force, velocity properties, and mechanical effectiveness in sprint running: Simple method to compute sprint mechanics’, *Scand J Med Sci Sports*, vol. 26, no. 6, pp. 648–658, Jun. 2016, doi: 10.1111/sms.12490.
- [22] S. A. Gard, S. C. Miff, and A. D. Kuo, ‘Comparison of kinematic and kinetic methods for computing the vertical motion of the body center of mass during walking’, *Human Movement Science*, vol. 22, no. 6, pp. 597–610, Apr. 2004, doi: 10.1016/j.humov.2003.11.002.
- [23] H.-M. Maus, A. Seyfarth, and S. Grimmer, ‘Combining forces and kinematics for calculating consistent centre of mass trajectories’, *Journal of Experimental Biology*, vol. 214, no. 21, pp. 3511–3517, Nov. 2011, doi: 10.1242/jeb.057422.
- [24] A. E. Minetti, C. Cisotti, and O. S. Mian, ‘The mathematical description of the body centre of mass 3D path in human and animal locomotion’, *Journal of Biomechanics*, vol. 44, no. 8, pp. 1471–1477, May 2011, doi: 10.1016/j.jbiomech.2011.03.014.
- [25] G. Pavei, E. Seminati, D. Cazzola, and A. E. Minetti, ‘On the Estimation Accuracy of the 3D Body Center of Mass Trajectory during Human Locomotion: Inverse vs. Forward Dynamics’, *Front. Physiol.*, vol. 8, Mar. 2017, doi: 10.3389/fphys.2017.00129.
- [26] G. Pavei, F. Salis, A. Cereatti, and E. Bergamini, ‘Body center of mass trajectory and mechanical energy using inertial sensors: a feasible stride?’, *Gait & Posture*, vol. 80, pp. 199–205, Jul. 2020, doi: 10.1016/j.gaitpost.2020.04.012.
- [27] J. Slawinski, B. Millot, N. Houel, and D. Dinu, ‘Use of an Inertial Measurement System to Calculate Maximal Power during Running Sprint Acceleration: Comparison with the Radar System’, *Proceedings*, vol. 49, no. 1, p. 23, Jun. 2020, doi: 10.3390/proceedings2020049023.
- [28] P. E. di Prampero, S. Fusi, L. Sepulcri, J. B. Morin, A. Belli, and G. Antonutto, ‘Sprint running: a new energetic approach’, *Journal of Experimental Biology*, vol. 208, no. 14, pp. 2809–2816, Jul. 2005, doi: 10.1242/jeb.01700.

- [29]J.-B. Morin, T. Jeannin, B. Chevallier, and A. Belli, ‘Spring-Mass Model Characteristics During Sprint Running: Correlation with Performance and Fatigue-Induced Changes’, *Int J Sports Med*, vol. 27, no. 2, pp. 158–165, Feb. 2006, doi: 10.1055/s-2005-837569.
- [30]J.-B. Morin, P. Edouard, and P. Samozino, ‘Technical Ability of Force Application as a Determinant Factor of Sprint Performance’, *Medicine & Science in Sports & Exercise*, vol. 43, no. 9, pp. 1680–1688, Sep. 2011, doi: 10.1249/MSS.0b013e318216ea37.
- [31]J.-B. Morin and P. Sève, ‘Sprint running performance: comparison between treadmill and field conditions’, *Eur J Appl Physiol*, vol. 111, no. 8, pp. 1695–1703, Aug. 2011, doi: 10.1007/s00421-010-1804-0.
- [32]N. Bezodis, A. I. Salo, and G. Trewartha, ‘Measurement Error in Estimates of Sprint Velocity from a Laser Displacement Measurement Device’, *Int J Sports Med*, vol. 33, no. 06, pp. 439–444, Jun. 2012, doi: 10.1055/s-0031-1301313.
- [33]J. Slawinski, V. Billat, J.-P. Koralsztein, and M. Tavernier, ‘Use of Lumbar Point for the Estimation of Potential and Kinetic Mechanical Power in Running’, *Journal of Applied Biomechanics*, vol. 20, no. 3, pp. 324–331, Aug. 2004, doi: 10.1123/jab.20.3.324.
- [34]I. Setuain, P. Lecumberri, J. P. Ahtiainen, A. A. Mero, K. Häkkinen, and M. Izquierdo, ‘Sprint mechanics evaluation using inertial sensor-based technology: A laboratory validation study’, *Scand J Med Sci Sports*, vol. 28, no. 2, pp. 463–472, Feb. 2018, doi: 10.1111/sms.12946.
- [35]M. H. A. Eames, A. Cosgrove, and R. Baker, ‘Comparing methods of estimating the total body centre of mass in three-dimensions in normal and pathological gaits’, *Human Movement Science*, vol. 18, no. 5, pp. 637–646, Oct. 1999, doi: 10.1016/S0167-9457(99)00022-6.
- [36]R. van den Tillaar, R. Nagahara, S. Gleadhill, and P. Jiménez-Reyes, ‘Step-to-Step Kinematic Validation between an Inertial Measurement Unit (IMU) 3D System, a Combined Laser+IMU System and Force Plates during a 50 M Sprint in a Cohort of Sprinters’, *Sensors*, vol. 21, no. 19, p. 6560, Sep. 2021, doi: 10.3390/s21196560.
- [37]J.-B. Morin, P. Samozino, M. Murata, M. R. Cross, and R. Nagahara, ‘A simple method for computing sprint acceleration kinetics from running velocity data: Replication study with improved design’, *Journal of Biomechanics*, vol. 94, pp. 82–87, Sep. 2019, doi: 10.1016/j.jbiomech.2019.07.020.
- [38]D. Roetenberg, H. Luinge, and P. Slycke, ‘Xsens MVN: Full 6DOF Human Motion Tracking Using Miniature Inertial Sensors’, p. 10, 2013.
- [39]M. R. Yeadon and M. Morlock, ‘The appropriate use of regression equations for the estimation of segmental inertia parameters’, *Journal of Biomechanics*, vol. 22, no. 6–7, pp. 683–689, Jan. 1989, doi: 10.1016/0021-9290(89)90018-3.
- [40]D. A. Winter, *Biomechanics and motor control of human movement*, 4th ed. Hoboken, N.J: Wiley, 2009.
- [41]J. Eng and D. Winter, ‘Estimations of the horizontal displacement of the total body centre of mass: considerations during standing activities’, *Gait & Posture*, vol. 1, no. 3, pp. 141–144, Sep. 1993, doi: 10.1016/0966-6362(93)90055-6.
- [42]M. J. Bland and D. Altman G., ‘Statistical methods for assessing agreement between two methods of clinical measurement’, *The Lancet*, vol. 327, no. 8476, pp. 307–310, Feb. 1986, doi: 10.1016/S0140-6736(86)90837-8.

- [43] W. G. Hopkins, S. W. Marshall, A. M. Batterham, and J. Hanin, 'Progressive Statistics for Studies in Sports Medicine and Exercise Science', *Medicine & Science in Sports & Exercise*, vol. 41, no. 1, pp. 3–12, Jan. 2009, doi: 10.1249/MSS.0b013e31818cb278.
- [44] M. Mukaka, 'A guide to appropriate use of Correlation coefficient in medical research', *Malawi Med J*, vol. 24, no. 3, pp. 69–71, Sep. 2012.
- [45] R. Nagahara, H. Kanehisa, and T. Fukunaga, 'Ground reaction force across the transition during sprint acceleration', *Scand J Med Sci Sports*, vol. 30, no. 3, pp. 450–461, Mar. 2020, doi: 10.1111/sms.13596.